

ANGLE VALVES



IDROS

DESCRIPTION

Angle valves are suitable for cold and hot water supply for any kind of sanitary systems, such as domestic, commercial, industry installations.

ADVANTAGES

- Wide range
- Raw materials complying with UBA LIST
- Available with metal and ABS handle

FIELDS OF APPLICATION

APPLICATIONS		T. min.	T. max	Max. pressure
	drinking water	+5°C	+80°C	10 bar
	hot sanitary water	+5°C	+80°C	10 bar

THREADS AND NUTS TIGHTENING

Ø	Thread coupling	N° Turns (+1/4)
Ø 8	3/8"	3/4
Ø 10	3/8"	3/4

REGULATIONS

- UNI EN 1254-2

Fittings comply with UNI EN 1254-2 law: "Plumbing fittings - Fittings with compression ends for use with copper tubes."

- UNI EN ISO 228-1:2003

Threads complies with UNI EN ISO 228-1:2003 law: "Piping thread for coupling not with tightness on the thread".

- D.M. 174 (06/04/2004)

Raw materials used are of high quality and comply with the Ministerial Decree N°174 dated 06/04/2004 concerning the materials and the items used in fixed installations for water collection, treatment and supply.

- Comply with 4MS, UBA List (BC group), DIN 50930/6 Dir. 2011/65/UE, 6C attachment III (RhOSII).

CERTIFICATIONS

COUNTRY	CERTIFICATION	COUNTRY	CERTIFICATION	COUNTRY	CERTIFICATION
					
					
					



GENERAL FITTINGS SPA

Via Golgi 73/75, 25064 Gussago (BS) - ITALY

te. +39 030 3739017

www.generalfittings.it